





Stückliste / Parts list

Pos.	Artikel-Nr.: <i>order number</i>	Bezeichnung <i>title</i>
1	1083345	Pyrometer CellaTemp PK 51 AF 1/I0 <i>Pyrometer CellaTemp PK 51 AF 1/I0</i>
2	1080257	Montagekombination PK 15-005 <i>Mounting PK 15-005</i>
3	1043813	Kabel VK 02/L AF 1 <i>Cable VK 02/L AF 1</i>

Gewicht: 2.000 Kg
Weight: 2.000 Kg

Seite 1 von 1
Page 1 of 1




Gewicht: 0.340 Kg

Weight: 0.340 Kg

Seite 1 von 2


Page 1 of 2



VK 02/L AF1 (5m)
nr./no.: 1043813




VK 02/L AF2 (10m)
nr./no.: 1048085



VK 02/L AF3 (25m)
nr./no.: 1082724





VK 02/R AF1 (5m)
nr./no.: 1069551



VK 03/A AF1 (5m)
nr./no.: 1086480



VK 03/A AF2 (10m)
nr./no.: 1086481



VK 03/R AF3 (20m)
nr./no.: 1086483

Flansch PK 20/F-70

flange PK 20/F-70

nr./no. 1068382

Unterlegscheibe Ø35mm

shim Ø35mm

nr./no.: 1069169

Bajonettverschluss PS 11/N AF5

Bayonet coupling PS 11/N AF5

nr./no. 1068546

Axialluftdüse PS 01/A AF1

Air purge PS 01/A AF1

nr./no. 560951

Saphir-Scheibenvorsatz PS 15/I AF1

Sapphire window PS 15/I AF1

nr./no. 1023960

Pyrometer

A-A

Ø100 mm

Ø70 mm

Ø11 mm

M30x1,5

ca. 361 mm

10 mm

46,8 mm

17,5 mm

M30x1,5

Schlauchtülle G1/8"

für Schlauch mit lichter Weite 8 bis 9 mm

Hose nozzle G1/8"

for hose with inner width 8 to 9 mm

Seite 1 von 1

Page 1 of 1

Gewicht: 1.370 Kg

Weight: 1.370 Kg

KELLER

www.keller.de/its

Montagekombination


Mounting

PK 15-005

Artikel-Nr.: 1080257

Ersteller: Neukötter


13.04.2018 Z-Index: 02



Belegung
Configuration

Pol
contacts

braun	an 1
brown	at 1
weiß	an 2
white	at 2
blau	an 3
blue	at 3
schwarz	an 4
black	at 4
grau	an 5
grey	at 5
Schirm durchgängig an Verschraubung	
Shield constantly at screw connection	



(Maßstab 3:1)

PUR-Kabel / *PUR cable*

Umgebungstemperatur [°C] / *Ambient temperature* -25...90, cULus: max. 75 °C


Schutzart / *Protection* IP 65 / IP 67

Gewicht: 0.220 Kg
Weight: 0.220 Kg

Seite 1 von 1
Page 1 of 1



- Headquarters
- Sales and Service Center
- Sales abroad



Keller HCW GmbH
Infrared Temperature Solutions (ITS)
Carl-Keller-Straße 2-10
49479 Ibbenbüren-Laggenbeck
Germany

www.keller.de/its
Tel. +49 (0) 5451 850
Fax +49 (0) 5451 85412
its@keller.de

Distributor



INOR Transmitter Oy
Unikkotie 13
FI-01300 Vantaa
Puhelin +358 10 4217900
Faksi +358 10 4217901
myynti@inor.fi